

## AMENDMENTS

### IN THE CLAIMS

- Sub D1*
1. (Previously Amended) A printing system comprising:  
a pulse-jet printhead including a nozzle, a manometer and lines configured to connect said printhead and manometer in parallel to a fluid source to be connected to a variable pressure compensation source, wherein said system is adapted to vary an output of said variable pressure compensation source to maintain a fluid level within said manometer in a predetermined range to maintain fluid pressure at said nozzle within a corresponding range.
2. (Original) The system of claim 1, further comprising a fluid source.
- C1*
3. (Previously Amended) The system of claim 2, further comprising a sensor to generate a signal in response to the fluid level within said manometer, and a control unit which generates a control signal for said variable pressure compensation source in response to said sensor signal.
4. (Previously Amended) The system of claim 1, further comprising a variable pressure compensation source.
5. (Original) The system of claim 1, further comprising a first valve at an exit of said manometer.
6. (Previously Amended) The system of claim 1, further comprising a second valve at an entrance to a fluid reservoir.
7. (Previously Amended) The system of claim 6, further comprising a supply vessel to feed a print medium to said fluid source, wherein the system is adapted for said feeding to occur during use of said pulse jet nozzle.
8. (Original) The system of claim 1, further comprising a print medium.

9. (Original) The system of claim 8, wherein said print medium comprises a biopolymers or precursor thereof.

10. (Original) A method of maintaining a desired pressure of a print medium at a pulse-jet nozzle comprising:

providing a system comprising a manometer connected to a fluid reservoir in parallel with said nozzle;

applying pressure to said fluid reservoir;

monitoring a fluid level in said manometer; and

adjusting said pressure applied to said fluid reservoir in response to changes in said manometer level.

11. (Original) The method of claim 10, wherein said pressure applied is negative pressure.

12. (Original) The method of claim 10, wherein said pressure applied is positive pressure.

13. (Original) The method of claim 10, further comprising attaching a fluid supply vessel to said fluid reservoir, and feeding a print medium from said fluid supply vessel to said fluid reservoir.

14. - 22. (Cancelled, without prejudice)

23. (Currently Amended) ~~The method of claim 20;~~ A method of replenishing a pulse-jet reservoir comprising:

providing a printing system comprising a pulse-jet printhead, a pressure gauge, a reservoir, and a fluid supply vessel, wherein said reservoir has an inlet line and an outlet line, said inlet line capped by a valve for connection to a fluid supply and said outlet line in fluid communication with said printhead, wherein said pressure gauge comprises a manometer, and wherein said fluid supply vessel is connected to said reservoir via a supply vessel line connected to said valve;

connecting said fluid supply vessel to said reservoir;

opening said valve, and

feeding print medium from said fluid supply vessel to said reservoir, wherein said print medium is fed under pressure to said reservoir during use of said pulse-jet nozzle, and

wherein said print medium a biopolymer or precursor thereof.

24. (Original) The method according to claim 23, wherein said method is a method of producing a biopolymer array.

25. (Original) A biopolymeric array produced according to the method of claim 24.

26. (Previously Amended) A method of detecting the presence of an analyte in a sample, said method comprising:

contacting (i) a biopolymeric array according to Claim 25 having a polymeric ligand that specifically binds to said analyte, with (ii) a sample suspected of comprising said analyte under conditions sufficient for binding of said analyte to a biopolymeric ligand on said array to occur; and detecting the presence of binding complexes on the surface of the said array to detect the presence of said analyte in said sample.

27. (Original) The method according to claim 26, wherein said method further comprises a data transmission step.

28. (Original) A method according to claim 27 wherein the data is communicated to a remote location.

29. (Original) A method comprising receiving data representing a result of a reading obtained by the method of claim 27.